Revision Date 05/11/2020 Print Date 02/11/2021 Version 3.1

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	BOARDWALK STAINLESS STEEL CLEANER BWK 347A 20N18OZ
Material number	:	0000000001041284
Manufacturer or supplier's d	eta	ils
Company	:	Boardwalk / Essendant Co.
Address	:	One Parkway North Deerfield, IL 60015
Telephone	:	844-828-5617

Emergency telephone numbers		
For SDS Information	:	844-828-5617
For a Medical Emergency	:	
For a Transportation Emergency	:	Chemtel: 1(800)255-3924

Recommended use of the chemical and restrictions on use

Recommended use :	Poli	shes
-------------------	------	------

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas	
Colour	light cream	
Odour	characteristic	

GHS Classification

Gases under pressure Skin sensitisation	: Liquefied gas : Category 1
GHS label elements	
Hazard pictograms	: Gas cylinder Gas cylinder Gas cylinder Exclamation mark
Signal word	: Warning
Hazard statements	: H280 Contains gas under pressure; may explode if heated. H317 May cause an allergic skin reaction.
Precautionary statements	: Prevention: P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Version 3.1

Revision Date 05/11/2020

Print Date 02/11/2021

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.
P251 Pressurized container: Do not pierce or burn, even after use. **Response:**P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse. **Storage:**P410 + P403 Protect from sunlight. Store in a well-ventilated place.
P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 30
propane	74-98-6	>= 1 - < 5
butane	106-97-8	>= 1 - < 5
Solvent naphtha (petroleum), medium aliph.	64742-88-7	>= 1 - < 5
citral	5392-40-5	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	 Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	 If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	 If skin irritation persists, call a physician. Wash off with soap and water. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes. Wash contaminated clothing before re-use.
In case of eye contact	 Rinse immediately with plenty of water for at least 15 minutes. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

Version 3.1	Revision Date 05/11/2020	Print Date 02/11/2021
If swallowed	 Keep respiratory tract clear. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. 	
Most important symptoms and effects, both acute and delayed	 Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. May cause an allergic skin reaction. Review section 2 of SDS to see all potential hazards. 	
Notes to physician	: Treat symptomatically. Symptoms	may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media Unsuitable extinguishing media	 Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet High volume water jet 	
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or wate courses.	ər
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods Further information	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Collect contaminated fire extinguishing water separately. The must not be discharged into drains. Fire residues and contaminated fire extinguishing water mube disposed of in accordance with local regulations. 	
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Ensure adequate ventilation. Remove all sources of ignition.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Version 3.1	Revision Date 05/11/2020	Print Date 02/11/2021	
Advice on safe handling	 Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the 		
Conditions for safe storage	application area. Dispose of rinse water in accordance with regulations. Always replace cap after use.		
Materials to avoid	No smoking. Keep in a dry, cool and well-ventilat Observe label precautions. Electrical installations / working mat the technological safety standards. Oxidizing agents		

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
citral	5392-40-5	TWA	5 ppm	ACGIH

Components with workplace control parameters

Version	3.1
10101011	0.1

Revision Date 05/11/2020 Print Date 02/11/2021

	(Inhalable fraction and vapor)	
Engineering measures	: effective ventilation in all processing areas	
Personal protective equipm	ent	
Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.	
Hand protection Material Remarks	Protective gloves The suitability for a specific workplace should be discussed with the producers of the protective gloves.	
Eye protection	Safety glasses Ensure that eyewash stations and safety showers are close to the workstation location.	
Skin and body protection	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.	
Hygiene measures	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	light cream
Odour	:	characteristic
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas, liquid)	:	The product is not flammable.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	0.938 g/cm3
Solubility(ies)		

Revision Date 05/11/2020

Print Date 02/11/2021

Water solubility	: partly soluble
Solubility in other solvents	: not determined
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: not determined
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Heat of combustion	: 15.00 kJ/g

Version 3.1

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials Hazardous decomposition products	: Oxidizing agents : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	 Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. May cause an allergic skin reaction. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH No component of this product present a equal to 0.1% is identified as a carcing carcinogen by ACGIH. OSHA No component of this product present a equal to 0.1% is no OSHA's list of regul NTP NTP No component of this product present a equal to 0.1% is identified as a known of by NTP. Acute toxicity Product: Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Components: Distillates (petroleum), hydrotreated light: Acute oral toxicity : LC50 Rat: > 5,000 mg/kg Acute inhalation toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product: Democking May inside to avec	Print Date 02/11/2021
OSHA No component of this product present a equal to 0.1% is identified as a carcinog carcinogen by ACGIH. NTP No component of this product present a equal to 0.1% is on OSHA's list of regul No component of this product present a equal to 0.1% is identified as a known of by NTP. Acute toxicity Product: Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Distillates (petroleum), hydrotreated light: Acute oral toxicity Acute oral toxicity : LD50 Rat: > 5,000 mg/l Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation : Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation : Product:	
OSHA No component of this product present a equal to 0.1% is on OSHA's list of regu NTP No component of this product present a equal to 0.1% is on OSHA's list of regu NTP No component of this product present a equal to 0.1% is identified as a known of by NTP. Acute toxicity Product: Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Components: Distillates (petroleum), hydrotreated light: Acute oral toxicity : LD50 Rat: > 5,000 mg/kg Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l Exposure time: 6 h : 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product: :	
NTP No component of this product present a equal to 0.1% is identified as a known of by NTP. Acute toxicity Product: Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Components: Distillates (petroleum), hydrotreated light: Acute oral toxicity : LD50 Rat: > 5,000 mg/lg Acute inhalation toxicity : LD50 Rat: > 4.6 mg/l Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product:	
Product: Acute oral toxicity Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Acute dermal toxicity Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Acute dermal toxicity Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Distillates (petroleum), hydrotreated light: Acute oral toxicity ILD50 Rat: > 5,000 mg/l Exposure time: 6 h Acute inhalation toxicity ILC50 Rat: > 4.6 mg/l Exposure time: 6 h ILD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product:	at levels greater than or
Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Components: Distillates (petroleum), hydrotreated light: Acute oral toxicity Acute inhalation toxicity : LD50 Rat: > 5,000 mg/l Exposure time: 6 h Acute dermal toxicity : LC50 Rat: > 4.6 mg/l Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product:	
Method: Calculation method Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/l Method: Calculation method Components: Distillates (petroleum), hydrotreated light: Acute oral toxicity : LD50 Rat: > 5,000 mg/l Exposure time: 6 h Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product:	
Method: Calculation method Components: Distillates (petroleum), hydrotreated light: Acute oral toxicity : LD50 Rat: > 5,000 mg/kg Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product:	kg
Distillates (petroleum), hydrotreated light: Acute oral toxicity : LD50 Rat: > 5,000 mg/kg Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product: Product:	kg
Acute oral toxicity : LD50 Rat: > 5,000 mg/kg Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product: Product:	
Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation <u>Product:</u> Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation <u>Product:</u>	
Exposure time: 6 h Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg Skin corrosion/irritation Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product: Product:	
Skin corrosion/irritation <u>Product:</u> Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation <u>Product:</u>	
Product: Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation Product:	
Remarks: May cause skin irritation and/or dermatitis. Serious eye damage/eye irritation <u>Product:</u>	
Serious eye damage/eye irritation <u>Product:</u>	
Product:	
Pomarka: May irritata ayaa	
Remarks: May irritate eyes.	
Respiratory or skin sensitisation	
Product:	
Remarks: Causes sensitisation.	
Components:	

citral: Classification: May cause sensitisation by skin contact.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Version 3.1

Revision Date 05/11/2020

Print Date 02/11/2021

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

Partition coefficient: n- octanol/water <u>Components:</u>	: Remarks: No data available
butane : Partition coefficient: n- octanol/water	: Pow: 2.89
citral : Partition coefficient: n- octanol/water	: log Pow: 2.9 (25 °C) Method: OECD Test Guideline 117

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Version 3.1	Revision Date 05/11/2020	Print Date 02/11/2021
Remarks	This product neither contains, r with a Class I or Class II ODS a Clean Air Act Section 602 (40 0 + B).	as defined by the U.S.
Additional ecological information	: An environmental hazard cannot event of unprofessional handlin aquatic life with long lasting effe	g or disposal., Harmful to

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with
	chemical or used container.
	Dispose of in accordance with local regulations.
Contaminated packaging	: Empty remaining contents.
	Dispose of as unused product.
	Do not re-use empty containers.
	Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

Version 3.1

Revision Date 05/11/2020

Print Date 02/11/2021

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Gases under pressure Respiratory or skin sensitisation
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	
	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 3.1

Revision Date 05/11/2020

Print Date 02/11/2021

Further information

NFPA:

HEALTH	3
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme


HMIS III:

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic



Version: 3.1

Version 3.1

Revision Date 05/11/2020

Print Date 02/11/2021

Revision Date:	05/11/2020
Print Date:	02/11/2021

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.